

Power to go

Compact and quiet, with the ability to power even the most sensitive electronic equipment, our Inverter range is trusted by professional and private users throughout the world.



Electric Start

Press the button to start the engine.



Fuel Injection Engine

A world first for small generators. The fuel injection system improves starting, increases efficiency and reduces emissions.



i-Monitor

Monitors output performance as well as self-diagnostics and servicing information.



Pure sine wave

Best for sensitive electronic equipment.



ECO-Throttle™

Automatically adjusts the engine speed to precisely match the load, to save fuel, extend engine life and give quieter operation.

EU70is



Super-Quiet



Transport Wheels



Lightweight



Parallel Operation



Convenient and Portable

Images for illustration purposes only. Model availability is dependant on country, do not hesitate to ask your local Honda dealer.

EU Series



	EU10i	EU22i	EU30is	EU30ik	EU70is
OUTPUT TECHNOLOGY	INVERTER	INVERTER	INVERTER	INVERTER	INVERTER
Type	Single phase	Single phase	Single phase	Single phase	Single phase
Maximum output (kVA)	1.0	2.2	3.0	3.0	7.0
Rated output (kVA)	0.9	1.8	2.8	2.8	5.5
Rated voltage (V)	230	230	230	230	230
Rated frequency (Hz)	50	50	50	50	50
Rated current (A)	3.9	7.8	12.2	12.2	23.9
DC rated output	12V/8.0A	12V/8.3A	12V/12A	12V/12A	-
Engine model	GXH50	GXR120	GX200	GX200	GX390
Engine type	4-Stroke, OHV**, 1 cylinder	4-Stroke, OHV**, 1 cylinder	4-Stroke, OHV**, 1 cylinder	4-Stroke, OHV**, 1 cylinder	4-Stroke, OHV**, 1 cylinder
Displacement (cm³)	49.4	121.0	196.0	196.0	389.0
Bore x stroke (mm)	41.8 x 36.0	60.0 x 43.0	68.0 x 54.0	68.0 x 54.0	88.0 x 64.0
Engine speed (rpm)	4,000-6,000 (5,500-6,500 with Eco-Throttle off)	4,500 max	3,800 max	3,800 max	3,600 max
Cooling system	Forced air	Forced air	Forced air	Forced air	Forced air
Ignition system	Transistor	Transistor	Transistor	Transistor	Transistor
Oil capacity (L)	0.25	0.40	0.55	0.55	1.10
Fuel tank capacity (L)	2.1	3.6	13.3	13.3	19.2
Starter system	Recoil	Recoil	Recoil and electric start	Recoil and electric start	Recoil and electric start
Length (mm)	451	512	658	658	Handle down: 848 Handle up: 1,198
Width (mm)	242	290	482	482	700
Height (mm)	379	425	570	570	721
Dry weight (kg)	13.0	21.1	61.2	61.2	118.1
Guaranteed sound power level – dB(A) (2000/14/EC, 2005/88/EC)	87	90	91	91	91