

LINE INTERACTIVE UPS

600VA













This UPS is specially designed for Personal Computer with multi-functions. Its light weight, compact design perfect fits to the limited working environment. The UPS is equipped with boost and buck AVR to stabilize input voltage range. It is also built-in with DC start function. This function enables the UPS to be started up without AC power supplied.

>>> Product Data Sheet

MODEL	SOFT MANAGER-i 600	
CAPACITY	VA/W	600VA/360W
INPUT	Voltage	230VAC
	Voltage Range	140-300VAC
	Frequency	>40 (Auto Sensing)
OUTPUT	Voltage	230VAC
	Voltage Regulation (Batt. Mode)	+/-10%
	Frequency	50Hz
	Frequency Regulation (Batt. Mode)	+/-1 Hz
	Output Waveform	Modified Sinewave
BATTERY	Battery Type	12V7Ah x 1
	Backup Time (at a PC load with 15" monitor)	10-15 minutes
	Recharge Time	6 hours to 90% after complete discharge
TRANSFER TIME	Typical	4-8 ms
INDICATOR	AC Mode	Green lighting
	Battery Mode	Yellow LED Flashing
	Fault Mode	Red LED Lighting
AUDIBLE ALARM	Backup Mode	Sounding every 10 seconds
	Low Battery	Sounding every second
	Overload	Sounding every 0.5 second
	Fault	Continuously sounding
PROTECTION	Full Protection	Discharge, overcharge, and overload protection
PHYSICAL	Dimension (mm), DXWXH	278X100X143
WEIGHT	Net Weight	4.4kgs
ENVIRONMENT	Operating Environment	0-40°C, 0-90 % relative humidity (non- condensing)
	Noise Level	Less than 40dB